

Eagle Shot



- Polypropylene Twisted

PROPERTY	DESCRIPTION	PL927
Primary Yarn Polymer	Polypropylene	PRESSURE TREATED 2X4 ANCHOR TO SLOPE SUBGRADE @ .5% CONCRETE CURB W/ 1/2*0 STANILESS TOWARDS COLLECTOR TRENCH STEELE EXPANSION ANCHORS [CEDTEXTLE FABRIC,
Yarn Cross Section	Polypropylene Twisted	RESILIENT SUPPACING ASPHALT
Standard Color	Golf Green	CLEAN AGGREGATE
UV Stabilized	Yes	AGGREGATE BY LYASH UNDER THE YASH UNDER
Fabric Construction	Tufted	her FLY ASH UNDER ASPHALT TWO F4 REBAR 9" PERFORATED COLLECTOR 40" -
Primary Backing	Dual Layered Woven Polypropylene	SUB-DRAIN THE OLDELETURY MIN. MIN. MIN. SUB-DRAIN THE OLDELETURY MIN. MIN. SUB-DRAIN INSTALL FILTER FARMER BELOW AGGREGATE BASE COURSE AND AT BOTTOM & SIDES OF TRENCH
Coating Type	SilverBack™ Polyurethane	
Perforations	Yes	EXISTING EQUIPMENT FOUNDATION GRADE LUMBER OR RECYCLED PLASTIC. ATTACH WITH
Polypropylene Yarn Denier/Ends	8200/1	S.S.CONCRET SCREWS & WASHERS @ 187 O.C. (Including)
Recommended Infill	7-9 lbs. Silica Sand	THOROUGHLY COMPACTED MATERIAL AT EDGE FREE DRAINING FINISHING STONE.
Pile Height	1"	LASER GRANE ONLY
Pile Weight	33 oz.	GEOTEXTILE FABRIC

APPLICATION

This is an excellent putting green product designed to hold shots from 70-100 yards. This product can be installed indoors or outdoors on concrete or a compacted aggregate base.











EQUIPMENT

*Custom colors available upon request

200 Howell Dr. Dalton GA 30721

www.sporturf.cor

800.798.1056



TESTING

EAGLE SHOT PL927

FINISHED FABRIC	ENGLISH	I SYSTEM	METRIC	SYSTEM	ASTM TEST
Nominal Specification	Value	Units	Value	Units	Method
Pile Height (Nominal)	1	ln.	25.40	mm.	D-5823
Face Weight	33	oz/yd²	1,119	g/m²	D-5848
Total Fabric Weight	60	oz/yd²	2,034	g/m²	D-5848
Primary Backing Weight	7.4	oz/yd²	251	g/m²	D-5848
Secondary Coating Weight	20	oz/yd²	678	g/m²	D-5848
Tuft Bind	>8	lbs.	>3.6	kg.	D-1335
Grab Tear Strength (Average)	>200	lbs.	>91	kg.	D-2256
Lead Content	<50	ppm	<50	ppm	D-2765
Total Yarn Linear Density	8,200	Denier	9,020	D-Tex	D-1577
Stitch Rate	17.5	Per 3"	22.925	Per 10 cm	D-5793
Machine Gauge	3/8"	In.	.95	cm	D-5793
Flammability	TEST	PASSED	TEST	PASSED	D-2859
Water Permeability w/Infill	>30	In/hr	>76	cm/hr	F-1551
Fabric Width	15	Ft.	4.6	М	None



It is the policy of SporTurf[™] to continuously improve it line of products. Therefore, SporTurf[™] reserves the right to change, modify or discontinue systems, specifications and accessories of all products at any time without notice or obligation to purchaser.