

This is a field product. This product should be installed outdoors on a compacted aggregate base. Custom designed for baseball, Fielder's Choice has the added durability designed to reduce infill splash and migration which is extremely important in gameplay.









CFB-

*Custom colors available upon request





200 Howell Dr. Dalton GA 30721 www.sporturf.com 800.798.1056

TESTING

FIELDER'S CHOICE 52

FINISHED FABRIC	ENGLISH SYSTEM		METRIC	SYSTEM	ASTM TEST
Nominal Specification	Value	Units	Value	Units	Method
Pile Height (Nominal)	1 7/8	In.	47.63	mm.	D-5823
Face Weight	52	oz/yd²	1763	g/m²	D-5848
Total Fabric Weight	79	oz/yd²	2678	g/m²	D-5848
Primary backing Weight	7.4	oz/yd²	251	g/m²	D-5848
Secondary Coating Weight Tuft	20	oz/yd²	678	g/m²	D-5848
Bind	>10	lbs.	>4.5	Kg.	D-1335
Grab Tear Strength (Average)	>200	lbs.	>91	Kg.	D-2256
Lead Content	<50	ppm	<50	ppm	D-2765
Total Yarn Linear Density Tensile	12,600	Denier	14,000	D-Tex	D-1577
Strength (Slit PE) Tensile	8	lbs.	3.63	Kg.	D-5034
Strength (Texturized PP) Stitch	3.7	lbs.	1.7	Kg.	D-789
Rate	11.0	Per 3"	14.41	Per 10 cm	D-5793
Machine Gauge	1/2	In.	1.27	Cm.	D-5793
Flammability	TEST	PASSED	TEST	PASSED	D-2859
Water Permeability w/infill	>30	In./Hr.	>72	Cm./Hr.	F-1551
Fiber Thickness (Slit PE)	9.4	mils	100	microns	D-3218
Fabric Width (ArmorLoc™ 3L)	15	Ft.	4.6	М	None



It is the policy of SporTurf[™] to continuously improve their line of products. Therefore, SporTurf[™] reserves the right to change, modify or discontinue systems, specifications and accessories of all products at any time without notice or obligation to purchaser.